DATASHEET

AKASISON ROOF OUTLET XL75 FOR CONCRETE GUTTER CLAD

ARTICLE CODE: 747803



According to EN 1253

Roof outlet for gutter for Akasison siphonic roof drainage systems.
With holes for application in concrete gutter clad.

Delivery includes:	Air baffle with integrated leaf guard (UV-stabilized). Connection to HDPE, clamp flange and knock-in bolts.
Application:	Concrete gutter clad.
Insulation thickness:	n.a
Connection to HDPE:	Electrofusion coupler d75 mm Code 410795.
Dimensions:	d1 = 75 mm. L = 55 mm. S = 120 mm. A = 180 mm.
Drilling core size:	Ø □ 110 mm.
Performance:	1-18,0 l/s.
Material:	ASA, stainless steel, PVC, HDPE.

Code	Type	Description	Weight (kg)
747803	Akasison XL75 CON COV	Concrete gutter clad	0,97

Water level*	25 mm	30 mm	35 mm	40 mm	45 mm	50 mm	55 mm
Performance [l/s]	7,0	11,7	13,9	17,4	18,0	18,0	18,0

* height measured from the underside of the leaf guard

Packaging:	1 piece
Discount group:	AD
Date:	02.2021

21/02/022